

09/19/00

JC685 U.S. PTO

UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket No. 826.1621/JDH

First Named Inventor or Application Identifier:

Yusaku FUJII

Express Mail Label No.

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

ADDRESS TO: **Assistant Commissioner for Patents**
Box Patent Application
Washington, DC 20231

1. ☒ Fee Transmittal Form
2. ☒ Specification, Claims & Abstract [Total Pages: 98]
3. ☒ Drawing(s) (35 USC 113) [Total Sheets: 31]
4. ☒ Oath or Declaration [Total Pages: 3]
 - a. ☒ Newly executed (original or copy)
 - b. ☐ Copy from a prior application (37 CFR 1.63(d)) (for continuation/divisional with Box 17 completed)
 - i. ☐ **DELETION OF INVENTOR(S)**
 Signed statement attached deleting inventor(s) named in the prior application, see 37 CFR 1.63(d)(2) and 1.33(b).
5. ☐ Incorporation by Reference (usable if Box 4b is checked)
 The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein.
6. ☐ Microfiche Computer Program (Appendix)
7. ☐ Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary)
 - a. ☐ Computer Readable Copy
 - b. ☐ Paper Copy (identical to computer copy)
 - c. ☐ Statement verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

8. ☒ Assignment Papers (cover sheet & document(s))
9. ☐ 37 CFR 3.73(b) Statement (when there is an assignee) [] Power of Attorney
10. ☐ English Translation Document (if applicable)
11. ☐ Information Disclosure Statement (IDS)/PTO-1449 [] Copies of IDS Citations
12. ☐ Preliminary Amendment
13. ☒ Return Receipt Postcard (MPEP 503) (Should be specifically itemized)
14. ☐ Small Entity Statement(s) [] Statement filed in prior application, status still proper and desired.
15. ☒ Certified Copy of Priority Document(s) (if foreign priority is claimed) (Japanese Appln. 11-271916, filed 9/27/99)
16. ☐ Other:

17. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information:[] Continuation [] Divisional [] Continuation-in-part (CIP) of prior application No: / **18. CORRESPONDENCE ADDRESS**

21171

PATENT TRADEMARK OFFICE

Staas & Halsey

jc515 U.S. PTO
 09/665159
 09/19/00

NEW APPLICATION FEE TRANSMITTAL

Attorney Docket No.	826.1621/JDH
Application Number	To be assigned
Filing Date	September 19, 2000
First Named Inventor	Yusaku FUJII

AMOUNT ENCLOSED	\$1762.00
-----------------	-----------

FEE CALCULATION (fees effective 12/29/99)

CLAIMS	(1) FOR	(2) NUMBER FILED	(3) NUMBER EXTRA	(4) RATE	(5) CALCULATIONS
	TOTAL CLAIMS	47 - 20 =	27	X \$ 18.00 =	\$ 486.00
	INDEPENDENT CLAIMS	10 - 3 =	7	X \$ 78.00 =	546.00
	MULTIPLE DEPENDENT CLAIMS (any number; if applicable)			+ \$260.00 =	
	BASIC FILING FEE				690.00
	Total of above Calculations =				\$ 1722.00
	Surcharge for late filing fee, Statement or Power of Attorney (\$130.00)				+
	Reduction by 50% for filing by small entity (37 CFR 1.9, 1.27 & 1.28).				-
	TOTAL FILING FEE =				\$ 1722.00
	Surcharge for filing non-English language application (\$130.00; 37 CFR 1.52(d))				+
	Recordation of Assignment (\$40.00; 37 CFR 1.21(h)(1))				40.00
	TOTAL FEES DUE =				\$ 1762.00

METHOD OF PAYMENT

- ☒ Check enclosed as payment.
- ☐ Charge "TOTAL FEES DUE" to the Deposit Account No., below.
- ☐ No payment is enclosed and no charges to the Deposit Account are authorized at this time.

GENERAL AUTHORIZATION

- ☒ If the above-noted "AMOUNT ENCLOSED" is not correct, the Commissioner is hereby authorized to credit any overpayment or charge any additional fees necessary to:

Deposit Account No.

19-3935

Deposit Account Name

STAAS & HALSEY LLP

- ☒ The Commissioner is also authorized to credit any overpayments or charge any additional fees required under 37 CFR 1.16 (filing fees) or 37 CFR 1.17 (processing fees) during the prosecution of this application, including any related application(s) claiming benefit hereof pursuant to 35 USC § 120 (e.g., continuations/divisionals/CIPs under 37 CFR 1.53(b) and/or continuations/divisionals/CPAs under 37 CFR 1.53(d)) to maintain pendency hereof or of any such related application.

SUBMITTED BY: STAAS & HALSEY LLP

Typed Name James D. Halsey, Jr.

Reg. No. 22,729

Signature

Date

September 19, 2000

APPLICATION FOR
UNITED STATES LETTERS PATENT
SPECIFICATION

INVENTOR(s): Yusaku FUJII

Title of the Invention: APPARATUS AND METHOD FOR MATCHING
FINGERPRINT

Apparatus and Method for Matching Fingerprint

Background of the Invention

Field of the Invention

5 The present invention relates to an apparatus and a method for matching a fingerprint.

Description of the Related Art

10 Recently, computers have been installed in various systems with identification equipment attracting much attention. Conventionally, an ID card or a password have been used as an authentication measure. However, they have many problems in security.

15 As an authentication measure more reliable than a password, a personal matching technique using biometric information has attracted much attention. When a user can be checked using biometric information unique to the user, the check result
20 is very reliable.

 One of the biometric information available in authenticating a user is a fingerprint. A fingerprint is said to have two features, that is, 'uniqueness' and 'invariability', and is an expected
25 authentication measure. Some research and

development have been performed on a personal matching system using a fingerprint these days.

The biometric information to be used in authenticating a user can be a fingerprint, a voiceprint, an iris, a vein network on the retina, a signature, etc. They can be measured by various sensors such as a CCD camera, etc., and converted into electronic information such as an image, etc. Then, various information processes are performed on the biometric information obtained by a sensor, and the information for identifying a user is extracted from biometric information. A user can be authenticated by matching the biometric key information with preliminarily registered biometric key information about each user.

A fingerprint can be considered as practical biometric information.

The surface of a person's finger is not smooth. Raised lines are called ridges. Ridges form various patterns unique to a person. Ridges have bifurcation points and ending points. Since each person has his or her own distribution of bifurcation points and ending points, these points are referred to as feature points of a fingerprints. The distribution of feature points are used as an

important measure for specifying a person. When a fingerprint matching process is performed, the position, type, direction of these feature points are checked to determine whether or not a fingerprint matches a reference fingerprint.

The conventional fingerprint matching process has been performed by checking the length of ridges between feature points (refer to, for example, the Japanese Laid-Open Patent Publication No.11-195119). However, it is not sufficient in some cases to check only the lengths of ridges. Therefore, it is expected to improve the performance of the fingerprint matching process. In the previous method, the data of the lengths of ridges is stored as a part of fingerprint data, but is hard to be stored efficiently. That is, the size of the fingerprint data tends to be larger.

Summary of the Invention

The present invention aims at providing a high-reliable fingerprint matching apparatus and method.

The apparatus according to the first aspect of the present invention is an apparatus for comparing an obtained first fingerprint with a

preliminarily registered second fingerprint, and determining whether or not they match each other. The apparatus includes: a ridge relation obtaining unit for obtaining the relation of the ridge containing a vicinal feature point near the feature point to be checked in a matching process performed on the first and the second fingerprints to the ridge containing the feature point to be checked in the matching process; and a matching unit for performing the matching process by searching the second fingerprint containing the vicinal feature point near the feature point to be checked in the matching process for the relation of the ridge containing the vicinal feature point to the ridge containing the feature point in the first feature point to be checked in the matching process.

The apparatus according to the second aspect of the present invention is an apparatus for comparing an obtained first fingerprint with a preliminarily registered second fingerprint, and determining whether or not they match each other. The apparatus includes: a virtual feature point generation unit for generating a virtual feature point by referring to the first and the second feature points; a ridge relation obtaining unit for obtaining

the relation of the ridge containing a virtual vicinal feature point near the feature point to be checked in a matching process performed on the first and the second fingerprints to the ridge containing the feature point to be checked in the matching process; and a matching unit for performing the matching process by searching the second fingerprint containing the virtual vicinal feature point near the feature point to be checked in the matching process for the relation of the ridge containing the virtual vicinal feature point to the ridge containing the feature point in the first feature point to be checked in the matching process.

The apparatus according to the third aspect of the present invention is an apparatus for comparing an obtained first fingerprint with a preliminarily registered second fingerprint, and determining whether or not they match each other. The apparatus includes: a virtual feature point generation unit for generating a virtual feature point by referring to the first and the second feature points; a ridge relation obtaining unit for obtaining the relations of the ridge containing a vicinal feature point near the feature point, and the ridge containing a virtual vicinal point to be checked

in a matching process performed on the first and the second fingerprints to the ridge containing the feature point to be checked in the matching process; and a matching unit for performing the matching process by searching the second fingerprint containing the vicinal feature point near the feature point to be checked in the matching process for the relation of the ridge containing the vicinal feature point to the ridge containing the feature point in the first feature point to be checked in the matching process, and for performing the matching process by searching the second fingerprint containing the virtual vicinal feature point near the feature point to be checked in the matching process for the relation of the ridge containing the virtual vicinal feature point to the ridge containing the feature point in the first feature point to be checked in the matching process, thereby determining whether or not the feature point to be checked is matching.

20 The method according to the first aspect of the present invention is a method for comparing an obtained first fingerprint with a preliminarily registered second fingerprint, and determining whether or not they match each other. The method
25 includes the steps of: (a) obtaining the relation

006659 091900

of the ridge containing a vicinal feature point near the feature point to be checked in a matching process performed on the first and the second fingerprints to the ridge containing the feature point to be checked in the matching process; and (b) performing the matching process by searching the second fingerprint containing the vicinal feature point near the feature point to be checked in the matching process for the relation of the ridge containing the vicinal feature point to the ridge containing the feature point in the first feature point to be checked in the matching process.

The method according to the second aspect of the present invention is a method for comparing an obtained first fingerprint with a preliminarily registered second fingerprint, and determining whether or not they match each other. The method includes the steps of: (a) generating a virtual feature point by referring to the first and the second feature points; (b) obtaining the relation of the ridge containing a virtual vicinal feature point near the feature point to be checked in a matching process performed on the first and the second fingerprints to the ridge containing the feature point to be checked in the matching process; and

(c) performing the matching process by searching the second fingerprint containing the virtual vicinal feature point near the feature point to be checked in the matching process for the relation of the ridge containing the virtual vicinal feature point to the ridge containing the feature point in the first feature point to be checked in the matching process.

The method according to the third aspect of the present invention is a method for comparing an obtained first fingerprint with a preliminarily registered second fingerprint, and determining whether or not they match each other. The method includes: (a) generating a virtual feature point by referring to the first and the second feature points; (b) obtaining the relations of the ridge containing a vicinal feature point near the feature point, and the ridge containing a virtual vicinal point to be checked in a matching process performed on the first and the second fingerprints to the ridge containing the feature point to be checked in the matching process; and (c) performing the matching process by searching the second fingerprint containing the vicinal feature point near the feature point to be checked in the matching process for the

relation of the ridge containing the vicinal feature point to the ridge containing the feature point in the first feature point to be checked in the matching process, and performing the matching process by searching the second fingerprint containing the virtual vicinal feature point near the feature point to be checked in the matching process for the relation of the ridge containing the virtual vicinal feature point to the ridge containing the feature point in the first feature point to be checked in the matching process, thereby determining whether or not the feature point to be checked is matching.

According to the present invention, a matching process is performed on a vicinal feature point near the feature point to be checked including the relation of the ridge containing the feature point to be checked. Therefore, fingerprints can be compared with high precision, which cannot be attained in a matching process performed only by comparing the position, the direction, and the type of the vicinal feature point with those of the feature point to be checked.

In addition, by generating a virtual feature point for comparison with the feature point to be checked, a matching process can be performed with

the ridge containing a vicinal feature point near
an actual feature point considered even if the actual
feature point may be changed due to the pressure
of a fingerprint or sweat. Therefore, the matching
5 process can be performed with a smaller influence
of a change in a feature point of a fingerprint.

Furthermore, the fingerprint matching process
can be performed with a smaller influence of the
distortion, defect, touching ridges, split, etc.
10 of a fingerprint by a combination use of the relation
of a ridge containing a feature point to be checked
and a virtual feature point.

Brief Description of the Drawings

15 FIG. 1 shows the definition of the direction
of a feature point;

FIG. 2 shows the matching method (1) according
to the first embodiment of the target feature point
according to the present invention;

20 FIG. 3 shows the matching method (2) according
to the first embodiment of the target feature point
according to the present invention;

FIG. 4 shows the data structure according to
the first embodiment of the present invention;

25 FIG. 5 is a flowchart (1) of the process

006760"EST3360

according to the first embodiment of the present invention;

FIG. 6 is a flowchart (2) of the process according to the first embodiment of the present invention;

FIG. 7 is a flowchart (3) of the process according to the first embodiment of the present invention;

FIG. 8 is a flowchart (4) of the process according to the first embodiment of the present invention;

FIG. 9 shows the second embodiment (1) of the feature point matching method according to the present invention;

FIG. 10 shows the second embodiment (2) of the feature point matching method according to the present invention;

FIG. 11 is a block diagram of the functions of the apparatus for realizing the first and second embodiments of the fingerprint matching method;

FIG. 12 is a flowchart of the procedure of operating the apparatus shown in FIG. 11;

FIG. 13 shows an example (1) of a virtual feature point (projected feature point);

FIG. 14 shows an example (2) of a virtual feature

00665159.091300

point (projected feature point);

FIG. 15 shows an example of the type of data structure;

FIG. 16 shows the fourth embodiment of the present invention in which the type of a feature point has been changed;

FIG. 17 shows another example of a change in type of feature point;

FIG. 18 shows an example of a data structure;

FIG. 19 shows a change in type of target feature point;

FIG. 20 is a flowchart (1) of the process according to the fourth and fifth embodiments of the present invention;

FIG. 21 is a flowchart (2) of the process according to the fourth and fifth embodiments of the present invention;

FIG. 22 is a flowchart (3) of the process according to the fourth and fifth embodiments of the present invention;

FIG. 23 is a flowchart (4) of the process according to the fourth and fifth embodiments of the present invention;

FIG. 24 is a flowchart (5) of the process according to the fourth and fifth embodiments of

006T60" 65T.9960

the present invention;

FIG. 25 shows a chain matching process (1);

FIG. 26 shows a chain matching process (2);

FIG. 27 is a flowchart of the process for
5 checking whether or not fingerprints match each other
as a pattern;

FIG. 28 shows the seventh embodiment of the
present invention;

FIG. 29 is a block diagram of the functions
10 of the apparatus for realizing the third through
the seventh embodiments of the present invention;

FIG. 30 is a flowchart of the procedure of the
operation of the apparatus shown in FIG. 29; and

FIG. 31 shows an example of the configuration
15 of the hardware required when the embodiments of
the present invention are realized using a program.

Description of the Preferred Embodiments

According to the embodiments of the present
20 invention, a matching process is performed on the
ridges in the vicinity of the feature point to be
checked by referring to the information about the
connection of ridges between one feature point to
be checked and another feature point, and the feature
25 point information about feature points related by

006750-6515960

the connection of ridges.

Furthermore, according to the embodiments of the present invention, when a feature point has the information about another related feature point, the information about another feature point is managed using an identifier assigned to each feature point.

According to the embodiments of the present invention, when a feature point is checked in a matching process, the feature information about a vicinal feature point is referred to. Therefore, the feature point can be checked in the matching process with high precision. Furthermore, since it is determined whether the type of vicinal feature point refers to an ending point or a bifurcation point, a matching process can be performed with high precision when a change from an ending point to a bifurcation point has occurred, or when a change from a bifurcation point to an ending point has occurred. As a result, the performance of a matching process can be largely improved.

In addition, since the feature point information is managed using the identifier of a feature point, plural pieces of data do not coexist, and fingerprint data can be efficiently represented,

thereby reducing the amount of fingerprint data.

There are ending points and bifurcation points in a ridge of a fingerprint. The distribution of ending points and bifurcation points depends on each person. Therefore, it can normally be determined whether or not two fingerprints match each other by comparing the distributions of ending points and bifurcation points between the two fingerprints. For example, when two fingerprints are compared, all feature points contained in each fingerprint are extracted, and each feature point is sequentially compared with a corresponding feature point. The feature points are compared with each other in position, type (ending point or bifurcation point), direction, etc. If they match in a predetermined range, it is determined that the corresponding feature points match each other. When two fingerprints are compared, it can be determined that the two fingerprint match each other if the ratio of the number of matching feature points to the total number of feature points exceed a predetermined value.

Conventionally, feature points are compared in position, type, and direction. However, the conventional method cannot attain sufficient

006T69 65T6960

matching performance, thereby requiring a
furthermore strict matching condition. For example,
there is a method of comparing the numbers of ridge
lines, the ridge lengths between feature points,
5 etc.

According to the embodiments of the present
invention, the information about ridges is used in
the matching process in addition to the position,
type, and direction of a feature point. Defined
10 below as an example is the direction of a feature
point.

FIG. 1 shows the definition of the direction
of a feature point.

The direction of a feature point is defined
15 by detecting the direction of a ridge contained in
the image of a fingerprint to be detected.

An example of a method for detecting the
direction of a ridge can be a method of detecting
the direction of a ridge in a Hough transform from
20 a thin line image of a fingerprint obtained by
thinning an input image of the fingerprint. Refer
to the Image Analysis Handbook (from Tokyo University
Publication) for a Hough transform on page 572
through 573. The method for detecting the direction
25 of a ridge includes the following steps.

- 1) generating a thin line image of a fingerprint from an obtained image of the fingerprint.
- 2) dividing a thin line image of a fingerprint into block areas of a size of the width of several thin lines.
- 3) performing a Hough transform on each block area of a thin line image of a ridge, and extracting a linear component to obtain the local direction of the ridge of the block from the extracted linear component.
- 4) obtaining the global direction of the ridge by averaging the directions of the ridges of a target block and a vicinal block.

Thus, the direction of a ridge is first detected.

Then, the direction of a feature point is set to be parallel to the direction of the ridge detected above regardless of an ending point and a bifurcation point. When a feature point is an ending point as indicated by 1 shown in FIG. 1, the direction of a ridge is defined as the direction of the feature point (ending point). When a feature point is a bifurcation point as indicated by 2 shown in FIG. 1, the direction of a larger number of ridges is defined as the direction of the feature point (bifurcation point).

FIG. 2 shows the first embodiment of the feature point matching method according to the present invention.

The feature point enclosed by a circle in the center shown in FIG. 2 is a feature point to be checked in a matching process, and is hereinafter referred to as a target feature point. The feature point enclosed by a square is located near the target feature point, and is hereinafter referred to as a vicinal feature point. The ridge connected to the target feature point is referred to as the 0-th ridge, and a ridge away by n ridges are referred to as the n -th ridge and the $-n$ -th ridge (n is a natural number, a sign indicates specified directions. In FIG. 2, the upward direction is set as the positive direction).

A target feature point has the information about a vicinal feature point connected to the m -th ridge (m is an integer). A matching process of the target feature point is performed by determining whether the vicinal feature points match. Since a matching process of the target feature point is performed by matching the vicinal feature points, the ridge structure in the vicinity of the target feature point is also checked in the matching process.

Hereinafter, the feature point connected to the m-th ridge is referred to as the m-th primary related feature point. A combination of the m-th ridge and the m-th primary related feature point is hereinafter referred to as relation information.

The words 'matching' and 'coincident' appear in the following descriptions. They refer to "matching" in a predetermined range.

FIGS. 2 and 3 show the method of performing the matching process according to the first embodiment of the present invention.

Assume that FIG. 2 shows a preliminarily registered fingerprint, and FIG. 3 shows a fingerprint to be checked in the matching process.

First, according to the present embodiment, the feature point of an input fingerprint matching each feature point of a registered fingerprint is searched for in probable combinations of feature points. Among the probable combinations, the combination marking the highest point is assumed to be the matching feature points. This process is performed conventionally. According to the present embodiment, the following method is furthermore adopted. Also in the embodiments described later, it is assumed that the conventional matching feature

point searching process is adopted. However, the present invention is not limited to the combination of a present method with the conventional matching feature point searching method.

5 In the feature point matching method according to the present embodiment, the feature point information about the m-th primary related feature point is assigned to each feature point. For example, FIG. 4 shows the data structure containing feature
10 point information. In FIG. 2, the data corresponding to the target feature point ID 11 contains the information about the following feature points ID 9 through ID 13.

 position of feature point
15 type of feature point (terminal point or bifurcation point)

 direction of feature point

 The 0-th ridge is connected to the feature point ID 10.

20 The first ridge is connected to the feature point ID 9.

 The second ridge is connected to the feature point ID 9.

 The minus first ridge is connected to the
25 feature point ID 12.

The minus second ridge is connected to the feature point ID 13.

Thus, the data of one feature point contains the information about the ridges connected to the feature point in addition to the information about the feature point itself. In addition, each feature point is managed by an identifier. If the information about, for example, the feature points ID 9 and ID 10 are required when the feature point ID 11 is checked, then data is retrieved using the ID 9 and the ID 10 as keys, and the entries of the feature points ID 9 and ID 10 are searched for. From the retrieved data, the information about the position, type, method, etc. of the feature points ID 9 and ID 10 is extracted. For example, the information can be as follows.

The feature point ID 9 is a bifurcation point (type) having the coordinate (100, 150), and is headed right.

The feature point ID 10 is a bifurcation point (type) having the coordinate (90, 160), and is headed left.

Similarly, the data corresponding to the target feature point shown in FIG. 3 contains the information about the feature points ID 1 through

ID 5, and the feature point information about them.

position of feature point

type of feature point

direction of feature point

5 The 0-th ridge is connected to the feature
point ID 2.

 The first ridge is connected to the feature
point ID 1.

 The second ridge is connected to the feature
10 point ID 1.

 The minus first ridge is connected to the
feature point ID 4.

 The minus second ridge is connected to the
feature point ID 5.

15 The target feature point shown in FIG. 2 and
the target feature point shown in FIG. 3 are matched
as follows.

 First, the 0-th primary related feature points
are matched. That is, if other feature points (ID
20 10 shown in FIG. 2 and ID 2 shown in FIG. 3) connected
to the 0-th ridges match each other, the relation
between the target feature points shown in FIGS.
2 and 3 is defined as 'matching'.

 The feature point ID 10 shown in FIG. 2 and
25 the feature point ID 2 shown in FIG. 3 can be matched

005760"6343950

in the conventional matching method. For example, if they match each other in position, type, and direction in the range of a predetermined value, then they are assumed to be the same feature points.

5 Similarly, the matching process is performed on the first, second, minus first, and minus second ridges. The n-th ridges for the target feature points shown in FIGS. 2 and 3 are matched as follows.

The ridge structures of the second ridges
10 match. (The ID 9 shown in FIG. 2 is the same feature point as the ID 1 shown in FIG. 3.)

The ridge structures of the first ridges match.
(The ID 9 shown in FIG. 2 is the same feature point as the ID 1 shown in FIG. 3.)

15 The ridge structures of the 0-th ridges match.
(The ID 10 shown in FIG. 2 is the same feature point as the ID 2 shown in FIG. 3.)

The ridge structures of the minus first ridges
20 match. (The ID 12 shown in FIG. 2 is the same feature point as the ID 4 shown in FIG. 3.)

The ridge structures of the minus second
ridges match. (The ID 13 shown in FIG. 2 is the same feature point as the ID 5 shown in FIG. 3.)

Finally, considering all matching states of
25 the ridge structures, it is determined whether or

not the target feature point of the registered fingerprint matches the target feature point of the input fingerprint.

The determining method can be, for example,
5 a point marking method. In matching the ridge structures, the ridges from the minus second ridges to the second ridges are matched respectively. If two corresponding ridge structures match each other, one point is marked. For example, if a total of 3
10 or more points are marked, then the target feature points are defined as 'matching'.

Thus, the relation information about the feature points is checked for each feature point. Finally, a total number of feature points is counted.
15 If the ratio of the number of matching feature points exceeds a predetermined value, if the number of matching feature points is larger than a predetermined value, or if the total mark of all matching feature points exceeds a predetermined
20 value in the feature points contained in the fingerprints, then it is determined that the fingerprints match each other.

In the above mentioned embodiment, although only one n-th (n is a positive number other than
25 0) ridge primary related feature point is selected

for each ridge, each n-th ridge has feature points at both ends. Therefore, the relation information about two primary related feature points can be recorded.

5 FIG. 2 shows the case containing a target feature point as an ending point. However, the similar matching process is performed on a bifurcation point. In the case of a bifurcation point, there are a total of 3 feature points connected
10 to the 0-th ridges. When the 0-th ridges are matched, all corresponding feature points connected to the 0-th ridges are matched in all combinations, and the highest mark is defined as the final mark of the feature point.

15 FIGS. 5 and 8 are flowcharts of the process according to the first embodiment.

A subroutine 1 matches the related feature points in the D-th ridges of the two feature points to be matched, and computes a total mark

20 A subroutine 2 computes a total mark of the 0-th ridge when a feature point to be checked is a bifurcation point. When the feature point is a bifurcation point, there are three 0-th ridges. Therefore, when the matching process is performed,
25 there are a total of six combinations of the 0-th

ridges of the feature points to be matched. For example, assuming that the 0-th ridges of the registered fingerprint are A, B, and C, and the 0-th ridges of the input fingerprint are P, Q, and R, the following combinations can be obtained.

(A - P, B - Q, C - R), (A - P, B - R, C - Q)
 (A - Q, B - P, C - R), (A - Q, B - R, C - P)
 (A - R, B - P, C - Q), (A - R, B - Q, C - P)

The total mark is computed for each combination, and the largest value of the computed points is defined as the total mark of the 0-th ridge. The subroutine 2 indicates the computation procedure.

In FIG. 5, it is determined in step S1 whether or not the feature points A and B, which are target feature points, are of the same type. If they are not of the same type, control is passed to the flowchart shown in FIG. 8. When they are of the same type, control is passed to step S2. It is determined in step S2 whether or not type of the feature points A and B is an ending point. In step S3, if the type of the feature points A and B is an ending point, then the return values of the subroutine 1 are added up, the total mark is computed, and control is passed to step S6. If it is determined in step S2 that the type of the feature points A and B is not an ending

point, then the return values of the subroutine 1 are added up for the ridges other than the 0-th ridges in step S4. The mark is computed by the subroutine 2 for the 0-th ridges in step S5, and the result is added to the mark obtained in step S4 to obtain the total mark. Then, it is determined whether or not the total mark is larger than a threshold in step S6. If it is larger than the threshold, then it is determined in step S7 that the feature points A and B match each other. If the total mark is equal to or smaller than the threshold, then it is determined in step S8 that the feature points A and B do not match each other.

FIG. 6 is a flowchart of the process performed by the subroutine 1 invoked in the process shown in FIG. 5.

When the subroutine 1 is invoked, the positions, types, and directions of the related feature points are obtained from the feature point identifiers of the D-th related feature points for the feature points A and B in step S9. It is determined in step S10 whether or not the positions and directions of the related feature points of the feature points A and B match each other. If they do not match, the mark is set to 0 in step S14. If the determination

result is YES in step S10, then it is determined in step S11 whether or not the types of the related feature points of the feature points A and B match each other. If it is determined in step S11 that the types do not match, then the mark is set to 0.5 in step S13. If it is determined in step S11 that the types match each other, the mark is set to 1 in step S12. Then, the mark is defined as a return value, and control is returned to the flowchart shown in FIG. 5 in step S15.

The mark is set to 0.5 when the types do not match each other because it is considered that the type of a feature point depends on the pressure of the finger onto the sensor when a fingerprint is taken for entry and when the fingerprint is input for a matching process, thereby obtaining a matching result from the fingerprints matching in position and direction, and not matching in type by setting 0.5.

FIG. 7 is a flowchart of the process performed by the subroutine 2 invoked in the process shown in FIG. 5.

In step S16, the combinations (no overlapping) of the 0-th ridges (3 ridges for each feature point) (the subroutine 2 is invoked when the feature

of the related feature points on the ending points
of the feature points A and B are lowered by 1. This
indicates that the ridges of each order is affected
when a feature point is converted from an ending
5 point to a bifurcation point, and from a bifurcation
point to an ending point. The detail explanation
is described later. Then, in step S23, the marks
S1 for the ridges other than the 0-th ridges are
computed by the subroutine 1 shown in FIG. 6. Then,
10 in step S24, the marks are computed for the 0-th
ridges by the subroutine 2 shown in FIG. 7, and the
results are added to the marks obtained in step S23.
In step S25, the order of the relation information
of the feature points A and B are returned to the
15 original values. Then, in step S26, the negative
orders of the related feature points of the ending
points in the feature points A and B are increased
by 1. Then, in step S27, the marks for the ridges
other than the 0-th ridges are computed by the
20 subroutine 1 shown in FIG. 6. Then, in step S28,
the marks are computed for the 0-th ridges by the
subroutine 2 shown in FIG. 7, and the results are
added to the marks computed in step S28 to obtain
the total mark S2. In step S29, the orders of the
25 relation information about the feature points A and

B are returned to the original values. In step S30, the value of S1 or S2, whichever is larger, is set as the mark S, and control is passed to step S6 shown in FIG. 5.

5 FIGS. 9 and 10 show the second embodiment of the feature point matching method according to the present invention.

10 FIG. 9 shows a preliminarily registered fingerprint, and FIG. 10 shows a fingerprint to be checked.

15 According to the second embodiment, the data of the number of ridges is added to the first embodiment. Described below is the feature point matching method using the data of the number of ridges.

20 As in the first feature point matching method, the matching process on the target feature point ID 7 shown in FIG. 9 is performed using a vicinal feature point. When the number of ridges between a target feature point and a vicinal feature point is n, the vicinal feature point is hereinafter referred to as an n-th vicinal feature point (n is an integer equal to or larger than 0).

25 A target feature point has information about the n-th vicinal feature point. The target feature

point is matched with the n-th vicinal feature point to determine whether or not they match each other. Since the target feature point is matched against the n-th vicinal feature point, the matching process
 5 on the target feature point is to check the ridge structure around the target feature point.

A target feature point has the information about the number of ridges to a vicinal feature point and the feature point information about the vicinal
 10 feature point. For example, in FIG. 9, the target feature point ID 7 has the following n-th vicinal feature point information.

The 0-th vicinal feature points are ID 6 and ID 9.

15 The first vicinal feature points are ID 5 and ID 8.

The second vicinal feature point is ID 10.

Together with the above mentioned information, the feature point information about the feature point
 20 of each identifier is stored. Examples are shown below.

The feature point of the ID 9 is a bifurcation point (type), has the coordinate (100, 150), and is headed right.

25 The feature point of the ID 10 is a bifurcation

point (type), has the coordinate (90, 180), and is headed down.

A target feature point is matched with each vicinal feature point.

5 First, the 0-th vicinal feature points are checked. The 0-th vicinal feature points are ID 3 and ID 6 in FIG. 10. Since the registered fingerprint and the input fingerprint have respective 0-th vicinal feature points, there are several
10 combinations of the 0-th vicinal feature points to be checked. Therefore, the matching process is performed on all combinations.

The combinations are listed below.

1. (matching the feature point ID 6 shown in FIG.
15 9 with the feature point ID 3 shown in FIG. 10) and (matching the feature point ID 9 shown in FIG. 9 with the feature point ID 6 shown in FIG. 10)
2. (matching the feature point ID 6 shown in FIG.
9 with the feature point ID 6 shown in FIG. 10) and
20 (matching the feature point ID 9 shown in FIG. 9 with the feature point ID 3 shown in FIG. 10)

The feature point matching process is performed as in the first feature point matching method. That is, the feature points are defined as
25 'matching' if they match in position, type, and

direction within the range of a predetermined value.
When a couple of vicinal feature points match each
other as in the first matching method, one point
is marked. In the combinations 1 and 2 above, the
5 mark of whichever is higher is defined as the matching
mark of the 0-th ridge structure.

Similarly, the matching process is performed
on the n-th vicinal feature point. When there are
a plurality of combinations to be checked, the
10 matching marks are computed for all combinations,
and the largest value is defined as the matching
mark of the n-th vicinal feature point.

It is determined whether or not target feature
points match each other by total marks as in the
15 first matching method.

According to the second embodiment, the
feature point matching process is performed also
using the number of ridges. The second embodiment
is realized by combining the feature point matching
20 method based on the number of ridges with the first
matching method. When the n-th related (vicinal)
feature point matching process is performed, the
feature points are matched with each other in each
method. If a matching result is output in either
25 of the methods, it is determined that the ridge

structures of the n -th ridges match each other. Although one piece of the relation information to the two vicinal feature points cannot be detected, the feature point matching process can be
 5 successfully performed. This is effective when the ridge structure of a fingerprint cannot be partially detected.

FIG. 11 is a block diagram of the functions of the apparatus for realizing the first and second
 10 embodiments of the fingerprint matching method.

A fingerprint scanner 13 is a fingerprint input device for measuring the pattern of a fingerprint as an image. An image storage unit 10 is a storage device for storing a fingerprint image being treated
 15 in an image process. An image binarization unit 12 converts a multivalued intensity level fingerprint image into a binary intensity level fingerprint image, and is well-known by one of ordinary skill in the art. An image thinning unit 11 extracts the core
 20 line of a ridge from the binarized fingerprint image. A feature point extraction unit 15 extracts a fingerprint feature point from a thinned fingerprint image. A feature point information extraction unit 16 detects each piece of feature point information
 25 (position, type, and direction) about a feature point

006T60" 65T59360

from a thinned image, and the direction of a feature point is detected based on the definition described by referring to FIG. 1. A primary relation information extraction unit 17 extracts the primary
 5 related feature point of each feature point from a thinned image. A fingerprint center position detection unit 14 detects the center position of a fingerprint. A fingerprint information storage unit 18 stores the obtained feature point information,
 10 the relation information, and the fingerprint center position as one piece of fingerprint information. A registered fingerprint information storage unit 20 stores preliminarily registered fingerprint information as a database. A fingerprint matching
 15 unit 19 checks two pieces of fingerprint information, and determines whether or not they match each other. A matching result display unit 21 displays a matching result.

Each of the above mentioned units is described
 20 below in detail in order of operation procedure.

FIG. 12 is a flowchart of the operation procedure of the apparatus shown in FIG. 11.

First, the fingerprint scanner 13 collects a multivalued fingerprint image (step S40). The
 25 collected multivalued fingerprint image is stored

in the image storage unit 10. The image binarization unit 12 binarizes the multivalued fingerprint image (step S41), and stores it in the image storage unit 10 again. The image thinning unit 11 performs a thinning process to obtain the core line of a fingerprint ridge from the binarized fingerprint image. The thinned fingerprint image is stored in the image storage unit 10 again. The fingerprint center position detection unit 14 detects the center of the fingerprint from the multivalued image, the binarized image, etc. (step S42). The method of detecting a fingerprint center can be any of various well-known conventional methods.

The feature point extraction unit 15 extracts the feature point position of the fingerprint from the thinned fingerprint image (step S43). The feature point information extraction unit 16 detects the feature point information about the position, the type, and the direction of the feature point from the feature point position and the thinned image (step S44). The primary relation information extraction unit 17 extracts a primary related feature point from the feature point position and the thinned image, and the relation information is detected (step S45).

The fingerprint information storage unit 18 obtains one piece of fingerprint information from the collected fingerprint center position, the feature point information, and the primary relation information, and stores the fingerprint information (step S46). The registered fingerprint information storage unit 20 stores a database in which preliminarily measured fingerprint information is registered.

10 The fingerprint matching unit 19 matches the generated fingerprint information with the preliminarily registered specific fingerprint information (step S47). It is determined whether or not the fingerprints match each other by matching
15 corresponding feature points as described above.

Described below in detail is the matching procedure. Hereinafter, the registered fingerprint information is referred to a registered fingerprint, and the fingerprint to be checked
20 whether or not it matches the registered fingerprint is referred to as an input fingerprint.

First, the registered fingerprint and a fingerprint to be checked are aligned. The position of the fingerprint image depends on each case of
25 taking a fingerprint image. Therefore, the feature

point positions cannot be checked unless a common coordinate axis can be set between the registered fingerprint and the input fingerprint. As a common coordinate axis, for example, a coordinate axis
5 having the center of a fingerprint as an origin is set. Otherwise, a common coordinate axis can be set by defining a specified feature point as an origin.

Then, the matching process is performed according to the first embodiment of the above
10 mentioned feature point matching method on each feature point.

The feature point matching process is performed on all combinations of feature points between a registered fingerprint and a feature point
15 information. The procedure of the feature point matching process is described below.

Step 1

A combination of a feature point of the registered fingerprint and a feature point of the
20 input fingerprint is selected.

Step 2

When the feature point coordinates of the registered fingerprint and the feature point coordinates of the input fingerprint do not match
25 within a predetermined range, it is determined that

the two feature points do not match, and control is returned to step 1.

Step 3

A combination of two feature points are checked
5 in the above mentioned first feature point matching method, and a matching mark is computed. When the matching mark exceeds a predetermined value, it is determined that the feature points match each other. Then, control is returned to step S1, and a feature
10 point matching process is performed on another combination of feature points. When matching feature points are detected, they are not checked again in the matching process.

In the above mentioned procedure, all feature
15 points are checked whether or not matching feature points exist. When the number of matching feature points finally exceeds a predetermined value, it is determined that the registered fingerprint matches the input fingerprint. In addition, the
20 method of determining matching fingerprints can be to determine them when the ratio of the number of feature points determined as matching each other to the total number of feature points exceeds a predetermined value, or when the total score of
25 feature point matching scores exceeds a

005T60"65T6960

predetermined value.

Then, in step S48, the matching result is displayed, and the process terminates.

Then, according to the third embodiment of the
5 feature point matching method, the matching process is performed using a virtual feature point. The basic matching method is the same as the first embodiment of the feature point matching method.

Before collecting the relation information
10 about a target feature point, a virtual feature point is set on an fingerprint image. In this example, it is defined that the virtual feature point is the position from which an existing feature point is projected onto adjacent ridges. The projecting
15 method can be to define as a virtual feature point the crossing point of the line vertical to a ridge from a feature point and the adjacent ridge. However, it is not necessary to always draw a line vertical to the ridge, but a diagonal line will do. Otherwise,
20 in quite a different method, a virtual feature point can be set on the adjacent ridge. That is, a corresponding virtual feature point can be provided in the adjacent ridge.

FIG. 13 shows an example of a virtual feature
25 point (projected feature point).

The identifier of the virtual feature point should match the identifier of the projected-from feature point. That is, the projected-from feature point information is used as the feature point information of the virtual feature point.

The target feature point shown in FIG. 13 has the following relation information. In addition, it has the virtual feature point information at another position of the fingerprint data.

10 The 0-th ridge is connected to the virtual feature point ID 9.

 The first ridge is connected to the virtual feature point ID 12.

15 The second ridge is connected to the virtual feature point ID 8.

 The minus first ridge is connected to the virtual feature point ID 13.

 The minus second ridge is connected to the virtual feature point ID 12.

20 FIG. 15 shows an example of the type of data structure.

 As shown in FIG. 15, the position, type, and direction are registered for the target feature point ID 11. Furthermore, the number of existing virtual feature points in the m-th (m is an integer) ridge

25

is registered.

The target feature point matching process is performed as in the first embodiment. Only a different point is that a feature point matching
5 process is performed on a virtual feature point in the present embodiment while the process is performed on the existing vicinal feature point according to the first embodiment.

The virtual feature point matching process is
10 performed on a projected-from feature point. For example, in FIG. 13, when the virtual feature point ID 12 is checked, it is matched with the actual feature point ID 12. If a matching result is output, then it is determined that the virtual feature point ID
15 12 is a matching point.

Other matching procedures are the same as those according to the first embodiment.

That is, when FIG. 13 shows a registered fingerprint, and FIG. 14 shows an input fingerprint,
20 a target feature point to be checked is determined first. It is the feature point ID 11 in FIG. 13, and the feature point ID 5 in FIG. 14. Then, it is checked in FIGS. 13 and 14 which virtual feature point is contained in the n-th ridge near the target
25 feature point. For example, in FIGS. 13 and 14, the

target feature points ID 11 and ID 5 have, as relation information, the virtual feature points existing in the ridges at the closest points respectively from the target feature points ID 11 and ID 5. In
5 FIGS. 13 and 14, the length of a ridge from the crossing point between the straight line vertical to the ridge from the target feature point and the ridge to the virtual feature point is checked, and the virtual feature point having the shortest ridge line is
10 adopted.

Then, the position, type, and direction of the ID 9 (FIG. 13) and the ID 2 (FIG. 14) in the 0-th ridges are checked, and the 0-th ridge is checked for matching. The process is sequentially
15 performed on the first ridge, second ridge,

Thus, by performing the matching process using a virtual feature point, a correct matching result can be obtained because the process is performed based on the relation to the vicinal ridges even
20 if the collection environments are different between a registered fingerprint and a fingerprint to be checked, and the ridges are distorted and changed slightly. According to the above mentioned embodiment, only one virtual feature point is
25 selected for each ridge. However, the number of

0066159.091900

selected virtual feature points is not limited, but two, three, or a different number of virtual feature points can be selected for each ridge and checked for matching.

5 The fingerprint matching method according to the third embodiment can be used with the process procedure according to the first embodiment as is except a matching process to be performed on the ridge structure by setting and using a virtual
10 feature point. Therefore, detailed descriptions are omitted here. According to the third embodiment, a matching process can be performed with higher precision by using the first and second embodiments in combination. An example of the combinational use
15 is described below by referring to the fourth embodiment.

Described below is the fourth embodiment of the feature point matching method according to the present invention.

20 In the fourth embodiment of the feature point matching method according to the present invention, the feature point matching process can be correctly performed even if the type of vicinal feature point has been changed.

25 When a fingerprint image is read by a

006760 6575960

006T60"5T5960
fingerprint scanner, the type of feature point depends on the state of the finger skin or the pressure of the finger. For example, a feature point is measured and output as an ending point when the finger
5 softly touches the fingerprint scanner, but it can be measured and output as a bifurcation point when the finger strongly presses the fingerprint scanner.

According to the fourth embodiment, the matching process is performed by assuming that the
10 type of feature point has been changed. Therefore, under such a type changing condition, the feature point matching process can be correctly performed.

The fourth embodiment is realized by combinational use with the first and third
15 embodiments.

Hereinafter, a feature point and a virtual feature point connected to the n-th ridge is respectively referred to as an n-th primary related feature point and an n-th secondary related feature
20 point.

FIG. 16 shows the fourth embodiment when the type of feature point has been changed.

The type of feature point may be changed when a ridge having an ending point as shown in FIG. 16A
25 touches an adjacent ridge. On the other hand, when

two touching ridged are disconnected, a bifurcation point is changed into an ending point.

An ending point is changed into a bifurcation point when the ridge having the ending point touches
5 an adjacent ridge. Therefore, a bifurcation point appears close to the point where the original ending point existed. If the directions of the ending point and the bifurcation point are defined as described by referring to FIG. 1, the directions of the ridges
10 of the feature points before and after the change are not different.

When the type of feature point is changed, for example, the 0-th primary related feature point as shown in FIG. 16B is changed into the 0-th secondary related feature point as shown in FIG. 16A. In
15 addition, when the primary related feature point shown in FIG. 16A is changed into an ending point, the first secondary related feature point appears as shown in FIG. 16B. That is, when a feature point
20 is changed, a primary related feature point is changed into a secondary related feature point while a secondary related feature point is changed into a primary related feature point in the ridge of the same order. In the feature point information, only
25 the type (ending point or bifurcation point) is

changed when the feature point is changed, but the coordinates and the direction hardly change.

That is, if a primary related feature point is matched with a secondary related feature point, the coordinates and the directions match within a predetermined range, and the types are different, then it indicates that the feature points have been changed, and the feature points are the same they initially were. Thus, the feature point matching process can be correctly performed even if a feature point is changed.

FIG. 17 shows another example of a change in type of feature point.

Assume that, as shown in FIG. 17A, the projected-from feature point of the 0-th secondary related feature point is an ending point, and touches the adjacent ridge as shown in FIG. 17B. In this case, the matching process outputs different types because the feature points match in position and direction. If the feature points completely match each other in position, direction, and type, then it is assumed that they are the same feature points. However, when they are different only in type, it is predicted that the feature point has been changed.

If it is determined that a feature point has

been changed as shown in FIGS. 16 and 17, it is assumed that the feature point is unstable, and a small point is marked in the feature point matching process.

An example of the feature point matching method is described below by referring to FIGS. 13 and 14. FIG. 13 shows a preliminarily registered fingerprint (registered fingerprint), and FIG. 14 shows a fingerprint (input fingerprint) to be checked.

As shown in the example of the data structure in FIG. 18, the data for the target feature point ID 11 stores the following information in the case shown in FIG. 13 in addition to the position, type, and direction of the ID 11 itself.

The primary and secondary related feature points of the 0-th ridge are respectively the ID 10 and the ID 9.

The primary and secondary related feature points of the first ridge are respectively the ID 9 and the ID 12.

The primary and secondary related feature points of the second ridge are respectively the ID 9 and the ID 8.

The primary and secondary related feature points of the minus first ridge are respectively the ID 12 and the ID 13.

The primary and secondary related feature points of the minus second ridge are respectively the ID 13 and the ID 12.

Similarly, the target feature point ID5 shown in FIG. 14 contains the following relation information.

The primary and secondary related feature points of the 0-th ridge are respectively the ID 3 and the ID 2.

The primary and secondary related feature points of the first ridge are respectively the ID 2 and the ID 4.

The primary and secondary related feature points of the second ridge are respectively the ID 1 and the ID 2.

There are no primary related feature point of the minus first ridge, and the secondary related feature point of the minus first ridge is the ID 4.

The primary and secondary related feature points of the minus second ridge are respectively the ID 6 and the ID 7.

First, the vicinal feature point matching processes are performed on the 0-th ridges.

As in the method according to the first and

third embodiments, the matching processes are performed between primary related feature points and between secondary related feature points. In this example, the 0-th vicinal feature point ID 10 shown in FIG. 13 is matched with the 0-th vicinal feature point ID 3 shown in FIG. 14, and the 0-th vicinal feature point ID 9 shown in FIG. 13 is matched with the 0-th vicinal feature point ID 2 shown in FIG. 14. Since the primary related feature points match each other, and the secondary related feature points match each other in the 0-th ridges in this case, the matching processes on the 0-th ridges are completed. Assuming that one point each is marked for each matching result, the matching mark of the 0-th ridges is 2.

Next, the matching processes are performed on the first ridges.

The matching processes are performed between primary related feature points and between secondary related feature points. In this example, the primary related feature point ID 9 shown in FIG. 13 is matched with the primary related feature point ID 2 shown in FIG. 14, and the secondary related feature point ID 12 shown in FIG. 13 is matched with the secondary related feature point ID 2 shown in

FIG. 14. In the matching process between the primary related feature point ID 9 shown in FIG. 13 and the primary related feature point ID 2 shown in FIG. 14, the feature points match in position and direction, but are different in type. Therefore, the matching results indicate that the feature point has been changed. As a result, the matching mark of the first primary related feature point is set to 0.5. Similarly, in the matching process between the secondary related feature point ID 12 shown in FIG. 13 and the secondary related feature point ID 4 shown in FIG. 14, the feature points match in position and direction, but are different in type. Therefore, the matching mark of the first secondary related feature point is also set to 0.5. Thus, the matching mark of the first ridge is a total of 1.

Then, the matching processes are performed on the second ridges.

In FIG. 13, the primary and secondary related feature points of the second ridge are respectively the ID 9 and the ID 8. In FIG. 14, the primary and secondary related feature points of the second ridge are respectively the ID 1 and the ID 2. Therefore, the matching process between the primary related feature points outputs a non-matching result.

Similarly, the matching process between the secondary related feature points also output a non-matching result, Then, assume that the feature point has been changed. That is, a matching process
5 is performed between the primary related feature point and the secondary related feature point.

The primary related feature point ID 9 of the second ridge shown in FIG. 13 is matched with the secondary related feature point ID 2 of the second
10 ridge shown in FIG. 14. In the matching process, the feature points match in position and direction, but are different in type. Since they are different in type, it is determined that the feature point has been changed. As a result, the matching mark
15 of the primary related feature point of the second ridge shown in FIG. 13 is set to 0.5.

Similarly, the secondary related feature point ID 8 of the second ridge shown in FIG. 13 is matched with the primary related feature point ID 1 of the
20 second ridge shown in FIG. 14. Also in this case, the feature points match in position and direction, but are different in type only. Therefore, it is determined that the feature point has been changed. As a result, the matching mark of the secondary
25 related feature point of the second ridge shown in

FIG. 13 is set to 0.5. Thus, the matching mark of the second ridge is a total of 1.

Thus, the similar matching processes are performed on the ridges of other orders. Finally, the matching mark of the target feature point is set as the total matching mark of each ridge. If the total matching mark exceeds a predetermined value, it is determined that the target feature point is matching.

Described below is the fifth embodiment of the feature point matching method according to the present invention. The fifth embodiment is an extension of the first through the fourth embodiments. That is, the matching performance is improved by adding the method described below to the first through the fourth embodiments.

According to the fifth embodiment, a feature point matching process can be correctly performed even when a target feature point is changed.

By adjusting the orders of ridges, target feature points can be matched with each other even when they are different in type between the registered fingerprint and the input fingerprint.

FIG. 19 shows the case in which the type of target feature point has been changed.

As shown in FIG. 19, when a target feature point is changed from an ending point to a bifurcation point, or from a bifurcation point to an ending point, the order of the ridge containing the primary related
5 feature point is shifted by 1.

For example, as shown in FIG. 19, when the target feature point which has been an ending point touches the first ridge, the first ridge turns to the 0-th ridge. Similarly, the positive order becomes
10 smaller by 1. On the other hand, when the target feature point which has been an ending point touches the minus first ridge, the minus first ridge turns to the 0-th ridge. Thus, the negative order becomes larger by 1.

15 The concept can be applied to the case in which a bifurcation point is changed into an ending point. Similarly, it can be applied to the case in which the number of ridges is counted.

Therefore, when a matching process is
20 performed on target feature points which are different in type, for example, the following steps are followed.

Step 1

Assume that a target feature point which is
25 an ending point touches the first ridge, and becomes

a bifurcation point, and that a target feature point matching process is performed. That is, the positive order of the ridge of a target feature point on the ending point side is reduced by 1, and the
5 matching mark is obtained in the method used when the target feature points of the same type are processed.

Step 2

Assume that a feature point which is an ending
10 point has been changed into a bifurcation point after it has touched the minus first ridge, and that a target feature point matching process is performed. That is, the negative order of the ridge is reduced by 1, and the matching mark is obtained in the method
15 used when the target feature points of the same type are processed.

Step 3

A matching mark whichever is larger between the above mentioned two matching marks is defined
20 as the final matching mark of the target feature point. In the method above, if the matching mark of the target feature point, then there is a strong possibility that the target feature points have been changed in the process of taking fingerprint images,
25 and the target feature points can be determined to

be the same feature points although they are different in type. The prediction may not be correct. In this case, a threshold can be strictly set for determination of the same feature points.

5 As described above, the process shown by the flowchart in FIG. 8 is performed by combining the fourth embodiment with the first embodiment.

FIGS. 20 through 24 are flowcharts of the processes according to the embodiments shown in FIGS.
10 4 and 5.

FIG. 20 is a flowchart of the main process.

First, in step S50, it is determined whether or not the target feature point A matches the target feature point B in type.

15 When they are different from each other in type, control is passed to the process shown in FIG. 23. When they match in type, then control is passed to step S51, and it is determined whether or not the type of the feature points A and B refers to an ending point.
20 If the type refers to an ending point, then control is passed to step S52, the image storage unit 10 is invoked, and the return value of the subroutine is added as a matching mark. When the addition is performed on the ridges of all orders,
25 control is passed to step S55.

If it is determined in step S51 that the type of the feature points A and B is not an ending point, then the marks are added up by the subroutine 10 for the ridges other than the 0-th ridges in step S53, the marks are added up for the 0-th ridges by the subroutine 11, and control is passed to step S55.

It is determined in step S55 whether or not the total mark is larger than a threshold. If it is larger than the threshold, then it is determined in step S56 that the feature points A and B match each other. If it is determined in step S55 that the total mark is equal to or smaller than the threshold, then it is determined that the feature points A and B do not match each other (step S57), thereby terminating the process.

FIGS. 21 and 22 are flowcharts of the process of the subroutine 10.

In step S58, the variable for setting a mark is initialized to 0. Then, it is determined in step S59 whether or not the feature points A and B match in position and direction of the D-th primary related feature point. If they match each other, it is determined in step S62. If YES in step S62, then one point is added to the mark S, and control is

passed to step S65. If it is determined in step S62 that they don't match in type, then 0.5 point is added to the mark, and control is passed to step S65.

- 5 If it is determined in step S59 that the feature points A and B do not match in position and direction of the D-th primary related feature point, then control is passed to step S60, and it is determined whether or not the feature points A and B match in
- 10 position and direction of the secondary related feature point. If they do not match, then control is passed to step S65. If it is determined in step S60 that they match in position and direction, then it is determined in step S61 whether or not the feature
- 15 points A and B match in type of the secondary related feature point. If YES, then control is passed to step S65 shown in FIG. 22. If NO, then control is passed to step S63, 0.5 point is added to the mark, and control is passed to step S65 shown in FIG. 22.
- 20 In step S65, it is determined whether or not the feature points A and B match in position and direction of the D-th secondary related feature point. If YES, then it is determined in step S68 whether or not the feature points A and B match in type of
- 25 the D-th secondary related feature point. If YES,

006150" 65T9960

then one point is added to the mark, and control is passed to step S71. If NO in step S68, then 0.5 point is added to the mark in step S69, and control is passed to step S71.

5 If it is determined in step S65 that the feature points A and B do not match in position and direction of the D-th secondary related feature point, then control is passed to step S66, and it is determined whether or not the feature points A and B match in
10 position and direction of the primary related feature point. If they do not match, then control is passed to step S71. If they match, then it is determined in step S67 whether or not the secondary related feature point of the feature point A matches the
15 primary related feature point of the feature point B match in type. If it is determined in step S67 that they do not match in type, then 0.5 point is added to the mark in step S69, and control is passed to step S71. If it is determined that they match
20 in type in step S67, then control is passed to step S71. In step S71, the mark S obtained in the processes above is used as a return value, and control is returned to the main process.

FIG. 23 is a flowchart of the process of the
25 subroutine 11.

When the subroutine 11 is invoked, combinations (no overlapping) of the 0-th ridges (3: in this case, the feature point is a bifurcation point) of the feature point A and the feature point

5 B are listed (H1 through Hn). In step S73, a combination Hi of the 0-th ridges is fetched. In step S74, a mark is computed by the subroutine 10 for the combination of ridges contained in the combination Hi of the 0-th ridges with the D set

10 to 0. The sum of the marks is substituted for the variable Si. Then, it is determined in step S75 whether or not the computation has been completed for all combinations. If not, control is returned to step S73, and the computation is performed on

15 other combinations. If it is determined in step S75 that the computation is completed for all combinations, then control is passed to step S76, the largest value in the marks Si obtained from the plurality of combinations is set as the mark S, and

20 the return value is set as the mark S in step S77, thereby returning to the main process.

FIG. 24 is a flowchart of the process performed when it is determined in step S50 that the feature points A and B do not match in type.

25 In step S78, the positive orders of the related

feature points as ending points are reduced by 1
 in the feature points A and B. Then, in step S79,
 the mark S1 is obtained by the subroutine 10 for
 the ridges other than the 0-th ridges. Then, in step
 5 S80, the mark is obtained by the subroutine 11 for
 the 0-th ridges, and the result is added to the S1
 to obtain a total mark of S1.

Then, in step S81, the orders of the relation
 information about the feature points A and B are
 10 returned to the original values. In step S82, the
 negative orders of the related feature points as
 ending points in the feature points A and B are
 incremented by 1.

Then, in step S83, the mark S2 is computed by
 15 the subroutine 10 for the ridges other than the 0-th
 ridges. Then, in step S84, the mark is computed by
 the subroutine 11 for the 0-th ridges, and the result
 is added to the previously obtained mark S2. In step
 S85, the orders of the relation information about
 20 the feature points A and B are returned to the original
 values. In step S86, the mark S1 or S2 whichever
 is larger is set as a total mark S, and control is
 passed to step S55.

FIGS. 25 and 26 show chain matching processes.

25 In the above mentioned embodiment, the

positions of two feature points fundamentally close to each other are compared with each other, and a feature point matching process is performed. Therefore, the feature point matching process is performed by comparing only local portions of the registered fingerprint and the input fingerprint. As a result, similar ridge structures in a local portion can be mistakenly recognized in the fingerprint matching process. To prevent this, the relation information matching process should be performed not on a local portion, but on a global area. To realize this, the feature points connected through relation information should match each other. When the matching feature points occur in a chain form, the matching mark is set to a large value. When the matching feature points occur in a chain form, a large value of a matching mark can be obtained by highly evaluating the matching result of ridge structures in a global area.

Described below in detail is the above mentioned process.

Some matching feature points can be detected even when two different fingerprints are checked. Therefore, it is necessary to set a threshold in determining whether or not two fingerprint match

5 which share some matching feature points.

that two feature points match each other when two n-th ridges are matched with each other in the embodiment according to the present invention. If the fingerprints result in the erroneous authentication, the matching portions of the target feature points are locally located, thereby satisfying a matching condition (FIG. 25 schematically shows this).

25 schematically shows this).

Therefore, to suppress the above mentioned erroneous authentication, it is checked whether or not a group of matching feature points appear. It is determined that a group of matching feature points appear by checking whether or not the matching feature points are connected through ridges.

FIG. 27 is a flowchart of the process of checking whether or not fingerprints match in a chain form as described above in the sixth embodiment of the present invention.

The flowchart in FIG. 27 shows an example of computing two rings of chain. In the fingerprint matching determination shown in FIG. 27, the number of matching fingerprints is not counted, but it is determined whether or not the total mark of matching feature points exceeds a matching determination threshold. The method of determining a matching result is not limited to the method shown in FIG. 27.

In step S90, the matching marks of all feature points are computed. Then, in step S91, one feature point is selected from among matching feature points to concentrate the matching process on one target feature point. In step S92, the number (n : n is a positive number) of matching feature points in the

related feature points of the selected feature point is counted. Then, in step S93, in the matching related feature points, the number (m : m is a positive number) of matching feature points of the related feature points is counted. In step S94, the matching mark of a target feature point is increased depending on the value of n and m . For example, it is multiplied by $(1 + 0.1n + 0.2m)$. It is determined in step S95 whether or not the computation has been completed for all feature points. If not, control is returned to step S91, and the computation is performed on the feature points for which the computation has not yet been performed. If it is determined in step S95 that the computation has been completed for all feature points, then the matching marks are obtained for all feature points in step S96, and it is determined in step S97 whether or not the total matching mark of feature points is larger than a predetermined threshold. If the total mark is equal to or smaller than the threshold, then it is determined in step S99 that the fingerprints do not match each other.

FIG. 28 shows the seventh embodiment of the present invention.

The relation information of a target feature

point is listed below based on the example shown in FIG. 28.

1) The vicinal feature point A is connected to the fourth ridge.

5 There are two ridges between the vicinal feature point A (also referred to as a connected feature point because it is connected to the fourth ridge) and the target feature point (the number of ridges between the vicinal feature point and the target feature point is detected from the fingerprint images in the above mentioned embodiment).

The type of a connected feature point is a bifurcation point.

2)

15 The vicinal feature point B ...

thus, similar information described in 1) above is obtained about each vicinal feature point.

When vicinal feature points are matched with each other, their relation information is matched with each other. That is, if the order of the ridge is equal to the number of ridges to a connected feature point and the forms of the connected feature points match each other when vicinal feature points are matched with each other, then it is determined that the ridge structures to the vicinal feature points

match. It is determined that target feature points match each other when the number of vicinal feature points exceeds a predetermined value.

According to the seventh embodiment, the
5 number of feature points in an area enclosed by the dotted line shown in FIG. 28 and the fourth ridge is confirmed. Thus, the order of ridges, the number of ridges, and the form of a feature point are fixed even when the deformation or the rotation of a
10 fingerprint changes, thereby stabilizing the matching process. That is, the matching process can be correctly performed against the deformation of a fingerprint depending on the pressure of the finger when it is pressed onto a scanner.

15 According to the present embodiment, the number of ridges between a connected feature point and a target feature point can be counted in various methods. For example, they can be the counting method of the above mentioned embodiment, the method
20 of including the ridge containing a connected feature point, the method of counting both ridges containing a connected feature point and a target feature point, the method of counting the ridge containing a target feature point, but not counting the ridge containing
25 a connected feature point, etc. The matching

performance can be improved when the vicinal feature point matching method according to the seventh embodiment is combined with the methods according to the first through the fifth embodiments.

5 FIG. 29 is a block diagram of the functions of the device for realizing the third through the seventh embodiments of the present invention.

10 In FIG. 29, the components also shown in FIG. 11 are assigned the same numbers as those assigned in FIG. 11, and the detailed explanation is omitted here.

15 With the configuration shown in FIG. 29, a virtual feature point generation unit 30 is provided in addition to the configuration shown in FIG. 11, and the primary relation information extraction unit is replaced with a primary/secondary relation information extraction unit 31. The fingerprint matching unit 19a realizes a matching method described above in the third through the sixth
20 embodiments. The virtual feature point generation unit 30 generates a virtual feature point from the input thinned fingerprint image and the information about a feature point extracted by the feature point extraction unit 15. In addition, the
25 primary/secondary relation information extraction

unit 31 determines the primary/secondary relation between feature points according to the thinned fingerprint image and the information about the virtual feature point.

5 FIG. 30 is a flowchart of the operation procedure of the apparatus shown in FIG. 29.

First, the fingerprint scanner 13 collects a multivalued fingerprint image (step S110). The collected multivalued fingerprint image is stored
10 in the image storage unit 10. The image binarization unit 12 binarizes the multivalued fingerprint image (step S111), and stores the result in the image storage unit 10 again. The image thinning unit 11 performs a thinning process to obtain the core of
15 a fingerprint ridge from the binarized fingerprint image. The thinned fingerprint image is stored in the image storage unit 10. The fingerprint center position detection unit 14 detects the center of a fingerprint from a multivalued image, a binarized
20 image, etc. (step S112). The method of detecting the center of a fingerprint can be selected from various conventional methods as described above.

The feature point extraction unit 15 extracts the position of a feature point of a fingerprint
25 from a thinned fingerprint image (step S113). The

feature point information extraction unit 16 detects the feature point information about the position, type, and direction of the feature point from the position of the feature point and the thinned image (step S114). The virtual feature point generation unit 30 generates the vicinal feature point from the feature point information and the thinned fingerprint image (step S115). The primary/secondary relation information extraction unit 31 extracts the primary/secondary relation between the feature point and the virtual feature point from the feature point information and the thinned image, and stores the primary/secondary relation information in the feature point information (step S116).

The fingerprint information storage unit 18 stores fingerprint information including the collected position of the center of the fingerprint, the feature point information, and the primary/secondary relation information (step S117). The registered fingerprint information storage unit 20 is a database in which preliminarily measured fingerprint information has been stored.

The fingerprint matching unit 19a matches generated fingerprint information with the

preliminarily registered specific fingerprint (step S118). The matching method can be any of the methods according to the third through the seventh embodiments described above.

5 Assuming that registered fingerprint information is referred to as a registered fingerprint, and a fingerprint to be checked whether or not it matches the registered fingerprint is referred to as an input fingerprint, the registered
10 fingerprint and the fingerprint to be checked are aligned first as described above by referring to FIG. 12, The position of the fingerprint in the fingerprint image depends on each time when a fingerprint image is taken. Therefore, the
15 positions of the feature points cannot be matched with each other unless the coordinate axis common between the registered fingerprint and the input fingerprint is set. As a common coordinate axis, for example, a coordinate axis having the center
20 of the fingerprint as its origin. Otherwise, a common coordinate axis can be set by using a specific feature point as an origin.

Then the subsequent processes are performed by appropriately combining the matching methods
25 described in the third through the seventh

006760" 6573960

embodiments. Since the matching methods according to the third through the seventh embodiments have been described above, the explanation is omitted here.

5 The process terminates in step S119 after displaying the matching result.

FIG. 31 shows an example of the hardware configuration required when the present embodiment is realized by a program.

10 The process of the above mentioned embodiment can be realized by a program operating in a general purpose computer 51. In this case, the general purpose computer 51 can be realized by devices, connected to a CPU 40 through a bus 41, mutually
15 exchanging data with one another. A BIOS, etc. is incorporated into ROM 42 to exchange data with an input/output device 50, etc. When the general purpose computer 51 is used as an exclusive fingerprint matching device, the CPU 40 can have
20 a program in the ROM 42. The input/output device 50 normally comprises a keyboard, a mouse, a display, etc., but a scanner for capturing a fingerprint image is required when a fingerprint matching process is performed.

25 Normally, the program can be stored in a storage

device 47 such as a hard disk, etc., developed in the RAM 43 at an instruction of the CPU 40 as necessary, and executed by the CPU 40. Otherwise, the program can be stored from the portable storage medium 49
5 (CD-ROM, Disket, DVD, etc, .) into the storage device 47, read from the storage device 47 to RAM 43, and executed by the CPU 40.

In the environment in which a computer network such as Internet, etc. has been highly developed,
10 a program can be connected to a network 45 through a communications interface 44, and can be downloaded from an information provider 46 for execution. Otherwise, as in a LAN, etc., when the information provider 46 functions as a server of a LAN, the CPU
15 40 can execute a program in a network environment without downloading the program directly from the information provider 46. In addition, data about a fingerprint can be transmitted to and processed by the information provider 46, and the general
20 purpose computer 51 can only receive the result.

A plurality of input/output devices 50 (especially a device for reading a fingerprint image) can be provided at several positions where a fingerprint matching process is to be performed,
25 and the matching process is performed by the general

purpose computer 51 mounted in the center.

A network of feature points connected through
ridges remains unchanged in structure even when a
fingerprint deforms, becomes expanded or contracted,
5 or partly lacks. Therefore, according to the
present invention, high matching performance can
be obtained using the ridge structure of fingerprints
and the positions of feature points.

00543-09190

What is claimed is:

1. An apparatus comparing an obtained first fingerprint with a preliminarily registered second fingerprint, and determining whether or not the fingerprints match each other, comprising:

a ridge relation obtaining unit obtaining relation of a ridge containing a vicinal feature point near a feature point to be checked in a matching process performed on the first and the second fingerprints to the ridge containing the feature point to be checked in the matching process; and

a matching unit performing the matching process by searching the second fingerprint containing the vicinal feature point near the feature point to be checked in the matching process for the relation of the ridge containing the vicinal feature point to the ridge containing the feature point in the first feature point to be checked in the matching process.

2. The apparatus according to claim 1, wherein said information about the feature point has a format comprising an identifier assigned to each feature point and corresponding feature information

about the feature point.

3. The apparatus according to claim 1, wherein
when a number of ridges from the feature point
5 to be checked to a ridge containing the vicinal
feature point, and when feature information about
the vicinal feature points matches in a predetermined
range, it is determined that feature points to be
checked contained in the first and the second
10 fingerprints are same feature points.

4. The apparatus according to claim 1, wherein
in said first and second fingerprint, when said
feature information about the vicinal feature points
15 matches in a predetermined range, a number of ridges
between the feature point to be checked and a ridge
containing the vicinal feature point matches a value
obtained by counting a number of ridges in an opposite
direction from the feature point to be checked to
20 the vicinal feature point, and a number of ridges
between the feature point to be checked and a ridge
containing the vicinal feature point matches a value
obtained by counting a number of ridges in a direction
from the feature point to be checked to the vicinal
25 feature point, it is determined that feature points

0066459 091900

the virtual vicinal feature point to the ridge containing the feature point in the first feature point to be checked in the matching process.

5 10. The apparatus according to claim 9, wherein
said information about the virtual feature
point has a format comprising an identifier assigned
to each virtual feature point and corresponding
feature information about the virtual feature point.

10

11. The apparatus according to claim 9, wherein
when a number of ridges from the feature point
to be checked to a ridge containing the virtual
vicinal feature point, and when feature information
15 about the virtual vicinal feature points matches
in a predetermined range, it is determined that
feature points to be checked contained in the first
and the second fingerprints are same feature points.

20 12. The apparatus according to claim 9, wherein
when said first and second fingerprints match
in at least one of position, type, and direction
of the virtual vicinal feature points, it is
determined that feature information of feature
25 points to be checked contained in the first and the

00655159, 091500

second fingerprints are same feature points.

13. The apparatus according to claim 9, wherein
when said feature points to be checked match
5 in position and direction in a predetermined range,
but are different in type in said first and second
fingerprints, a resultant matching level is low.

14. The apparatus according to claim 9, wherein
10 when said virtual vicinal feature points match
in position and direction in a predetermined range,
but are different in type in said first and second
fingerprints, a resultant matching level is low.

15 15. The apparatus according to claim 9, wherein
said virtual feature point is generated by
projecting an existing feature point to a vicinal
ridge.

20 16. The apparatus according to claim 15, wherein
feature information about the virtual feature
point is feature information about a feature point
from which a virtual feature point is projected.

25 17. The apparatus according to claim 9, wherein

006760" 15159960

when said feature points to be checked are different in type in said first and second fingerprints, a matching process is performed by changing relation between ridges containing the feature points to be checked and ridges containing the vicinal feature points.

18. An apparatus comparing an obtained first fingerprint with a preliminarily registered second fingerprint, and determining whether or not the fingerprints match each other, comprising:

a virtual feature point generation unit generating a virtual feature point by referring to the first and the second feature points;

a ridge relation obtaining unit obtaining relations of a ridge containing a vicinal feature point near a feature point, and a ridge containing the virtual vicinal point to be checked in a matching process performed on the first and the second fingerprints to the ridge containing the feature point to be checked in the matching process; and

a matching unit performing the matching process by searching the second fingerprint containing the vicinal feature point near the feature point to be checked in the matching process for the

09665459 091500

relation of the ridge containing the vicinal feature point to the ridge containing the feature point in the first feature point to be checked in the matching process, and performing the matching process by searching the second fingerprint containing the virtual vicinal feature point near the feature point to be checked in the matching process for the relation of the ridge containing the virtual vicinal feature point to the ridge containing the feature point in the first feature point to be checked in the matching process, thereby determining whether or not the feature point to be checked is matching.

19. The apparatus according to claim 18, wherein when said feature point to be checked matches in position and direction in said first and second fingerprints in a predetermined range, but does not match in type, evaluation of a matching result is set low.

20. The apparatus according to claim 18, wherein when said vicinal feature point or said virtual feature point matches in position and direction in a predetermined range in the first and second fingerprints, but does not match in type, evaluation

of a matching result is set low.

21. The apparatus according to claim 20, wherein
a matching process is performed on a
5 combination of the vicinal feature point of said
first and second fingerprint and the virtual feature
point.

22. The apparatus according to claim 18, wherein
10 when said first and second fingerprints match
in feature points to be checked and said vicinal
feature points match several times for the feature
points to be checked, evaluation of a matching result
is enhanced depending on a number of matching
15 results.

23. A method for comparing an obtained first
fingerprint with a preliminarily registered second
fingerprint, and determining whether or not the
20 fingerprints match each other, comprising:

(a) obtaining relation of a ridge containing
a vicinal feature point near a feature point to be
checked in a matching process performed on the first
and the second fingerprints to the ridge containing
25 a feature point to be checked in the matching process;

and

(b) performing the matching process by searching the second fingerprint containing the vicinal feature point near the feature point to be checked in the matching process for the relation of the ridge containing the vicinal feature point to the ridge containing the feature point in the first feature point to be checked in the matching process.

10

24. The method according to claim 23, wherein said information about the feature point has a format comprising an identifier assigned to each feature point and corresponding feature information about the feature point.

15

25. The method according to claim 23, wherein when a number of ridges from the feature point to be checked to a ridge containing the vicinal feature point, and when feature information about the vicinal feature points matches in a predetermined range, it is determined that feature points to be checked contained in the first and the second fingerprints are same feature points.

25

09665159 091900

26. The method according to claim 23, wherein
in said first and second fingerprint, when said
feature information about the vicinal feature points
matches in a predetermined range, a number of ridges
5 between the feature point to be checked and a ridge
containing the vicinal feature point matches a value
obtained by counting a number of ridges in an opposite
direction from the feature point to be checked to
the vicinal feature point, and a number of ridges
10 between the feature point to be checked and a ridge
containing the vicinal feature point matches a value
obtained by counting a number of ridges in a direction
from the feature point to be checked to the vicinal
feature point, it is determined that feature points
15 to be checked contained in the first and the second
fingerprints are same feature points.

27. The method according to claim 23, wherein
when said first and second fingerprints match
20 in at least one of position, type, and direction
of the vicinal feature points, it is determined that
feature information of feature points to be checked
contained in the first and the second fingerprints
are same feature points.

28. The method according to claim 23, wherein
when said feature points to be checked match
in position and direction in a predetermined range,
but are different in type in said first and second
5 fingerprints, a resultant matching level is low.

29. The apparatus according to claim 23, wherein
when said vicinal feature points match in
position and direction in a predetermined range,
10 but are different in type in said first and second
fingerprints, a resultant matching level is low.

30. The apparatus according to claim 23, wherein
when said feature points to be checked are
15 different in type in said first and second
fingerprints, a matching process is performed by
changing relation between ridges containing the
feature points to be checked and ridges containing
the vicinal feature points.

20

31. A method for comparing an obtained first fingerprint with a preliminarily registered second fingerprint, and determining whether or not the fingerprints match each other, comprising:

25 (a) generating a virtual feature point by

referring to the first and the second feature points;

(b) obtaining the relation of the ridge containing a virtual vicinal feature point near the feature point to be checked in a matching process performed on the first and the second fingerprints to the ridge containing the feature point to be checked in the matching process; and

(c) performing the matching process by searching the second fingerprint containing the virtual vicinal feature point near the feature point to be checked in the matching process for the relation of the ridge containing the virtual vicinal feature point to the ridge containing the feature point in the first feature point to be checked in the matching process.

32. The method according to claim 31, wherein said information about the virtual feature point has a format comprising an identifier assigned to each virtual feature point and corresponding feature information about the virtual feature point.

33. The method according to claim 31, wherein when a number of ridges from the feature point to be checked to a ridge containing the virtual

vicinal feature point, and when feature information about the virtual vicinal feature points matches in a predetermined range, it is determined that feature points to be checked contained in the first and the second fingerprints are same feature points.

34. The method according to claim 31, wherein when said first and second fingerprints match in at least one of position, type, and direction of the virtual vicinal feature points, it is determined that feature information of feature points to be checked contained in the first and the second fingerprints are same feature points.

35. The method according to claim 31, wherein when said feature points to be checked match in position and direction in a predetermined range, but are different in type in said first and second fingerprints, a resultant matching level is low.

20

36. The method according to claim 31, wherein when said virtual vicinal feature points match in position and direction in a predetermined range, but are different in type in said first and second fingerprints, a resultant matching level is low.

37. The method according to claim 31, wherein
said virtual feature point is generated by
projecting an existing feature point to a vicinal
5 ridge.

38. The method according to claim 37, wherein
feature information about the virtual feature
point is feature information about a feature point
10 from which a virtual feature point is projected.

39. The method according to claim 17, wherein
when said feature points to be checked are
different in type in said first and second
15 fingerprints, a matching process is performed by
changing relation between ridges containing the
feature points to be checked and ridges containing
the vicinal feature points.

20 40. A method for comparing an obtained first
fingerprint with a preliminarily registered second
fingerprint, and determining whether or not the
fingerprints match each other, comprising:

(a) generating a virtual feature point by
25 referring to the first and the second feature points;

006T60" 55T54450

(b) obtaining relations of a ridge containing a vicinal feature point near the feature point, and a ridge containing a virtual vicinal point to be checked in a matching process performed on the first and the second fingerprints to the ridge containing the feature point to be checked in the matching process; and

(c) performing the matching process by searching the second fingerprint containing the vicinal feature point near the feature point to be checked in the matching process for the relation of the ridge containing the vicinal feature point to the ridge containing the feature point in the first feature point to be checked in the matching process, and performing the matching process by searching the second fingerprint containing the virtual vicinal feature point near the feature point to be checked in the matching process for the relation of the ridge containing the virtual vicinal feature point to the ridge containing the feature point in the first feature point to be checked in the matching process, thereby determining whether or not the feature point to be checked is matching.

41. The method according to claim 40, wherein

when said feature point to be checked matches
in position and direction in said first and second
fingerprints in a predetermined range, but does not
match in type, evaluation of a matching result is
5 set low.

42. The method according to claim 40, wherein
when said vicinal feature point or said virtual
feature point matches in position and direction in
10 a predetermined range in the first and second
fingerprints, but does not match in type, evaluation
of a matching result is set low.

43. The method according to claim 42, wherein
15 a matching process is performed on a
combination of the vicinal feature point of said
first and second fingerprint and the virtual feature
point.

20 44. The method according to claim 40, wherein
when said first and second fingerprints match
in feature points to be checked and said vicinal
feature points match several times for the feature
points to be checked, evaluation of a matching result
25 is enhanced depending on a number of matching

006160" 6315950

results.

45. A computer-readable storage medium storing a program for directing a computer to realize a method for comparing an obtained first fingerprint with a preliminarily registered second fingerprint, and determining whether or not the fingerprints match each other, comprising:

(a) obtaining relation of a ridge containing
10 a vicinal feature point near a feature point to be
checked in a matching process performed on the first
and the second fingerprints to the ridge containing
a feature point to be checked in the matching process;
and

15 (b) performing the matching process by
searching the second fingerprint containing the
vicinal feature point near the feature point to be
checked in the matching process for the relation
of the ridge containing the vicinal feature point
20 to the ridge containing the feature point in the
first feature point to be checked in the matching
process.

46. A computer-readable storage medium storing a
25 program for directing a computer to realize a method

for comparing an obtained first fingerprint with a preliminarily registered second fingerprint, and determining whether or not the fingerprints match each other, comprising:

- 5 (a) generating a virtual feature point by referring to the first and the second feature points;
- (b) obtaining the relation of the ridge containing a virtual vicinal feature point near the feature point to be checked in a matching process
- 10 performed on the first and the second fingerprints to the ridge containing the feature point to be checked in the matching process; and
- (c) performing the matching process by searching the second fingerprint containing the
- 15 virtual vicinal feature point near the feature point to be checked in the matching process for the relation of the ridge containing the virtual vicinal feature point to the ridge containing the feature point in the first feature point to be checked in the matching
- 20 process.

47. A computer-readable storage medium storing a program for directing a computer to realize a method for comparing an obtained first fingerprint with

25 a preliminarily registered second fingerprint, and

005760" 6575960

determining whether or not the fingerprints match each other, comprising:

(a) generating a virtual feature point by referring to the first and the second feature points;

5 (b) obtaining relations of a ridge containing a vicinal feature point near the feature point, and a ridge containing a virtual vicinal point to be checked in a matching process performed on the first and the second fingerprints to the ridge containing
10 the feature point to be checked in the matching process; and

(c) performing the matching process by searching the second fingerprint containing the vicinal feature point near the feature point to be checked
15 in the matching process for the relation of the ridge containing the vicinal feature point to the ridge containing the feature point in the first feature point to be checked in the matching process, and performing the matching process by searching the
20 second fingerprint containing the virtual vicinal feature point near the feature point to be checked in the matching process for the relation of the ridge containing the virtual vicinal feature point to the ridge containing the feature point in the first
25 feature point to be checked in the matching process,

00665459.091900

Abstract of the Disclosure

After thinning a fingerprint image in a conventional method, a feature point is detected.

5 The feature point is assigned an ID, and the information about each feature point is managed. The information about a target feature point stores the information indicating the position of the ridge containing a vicinal feature point relative to the

10 position of the ridge containing the target feature point in addition to the position, type, and direction of the target feature point itself. Then, the information about the target feature point is checked in a matching process, and the vicinal

15 feature point is also checked in the matching process on a feature point contained in a ridge matching in position the ridge of the target feature point. When the target feature point and the vicinal feature point match each other in position and direction,

20 and are different from each other in type only, the mark is reduced to a value indicating a matching level. Then, a matching result of the vicinal feature points is obtained as a matching mark, and it is determined whether or not the target feature

25 point is matching by determining whether or not the

matching mark is equal to or larger than a threshold.

005150 6313960




FIG. 1




FIG. 2




FIG. 3

ID11
POSITION
TYPE
DIRECTION
O-TH : ID10 FIRST : ID9 SECOND : ID9 MINUS FIRST : ID12 MINUS SECOND : ID13
ID12
POSITION
TYPE
DIRECTION
O-TH : - - - - - FIRST : - - - - -

⋮

FIG. 4




FIG. 5




FIG. 6

005760" 65759560




FIG. 7

```

graph TD
    1((1)) --> S22[REDUCING POSITIVE ORDER OF RELATED FEATURE POINT OF END POINT IN FEATURE POINTS A AND B BY 1]
    S22 --> S23[MARKS1 = Σ ORDER D ≠ 0 (RETURN VALUE OF SUBROUTINE 1)]
    S23 --> S24[MARK S1 = S1 + (RETURN VALUE OF SUBROUTINE 2 ABOUT 0-TH RIDGE)]
    S24 --> S25[RETURNING ORDER OF RELATION INFORMATION OF FEATURE POINTS A AND B TO ORIGINAL VALUE]
    S25 --> S26[INCREASING POSITIVE ORDER OF RELATED FEATURE POINT OF END POINT IN FEATURE POINTS A AND B BY 1]
    S26 --> S27[MARK S2 = Σ ORDER D ≠ 0 (RETURN VALUE OF SUBROUTINE 1)]
    S27 --> S28[MAR S2 = S2 + (RETURN VALUE OF SUBROUTINE 2 ABOUT 0-THE RIDGE)]
    S28 --> S29[RETURNING ORDER OF RELATION INFORMATION OF FEATURE POINTS A AND B TO ORIGINAL VALUE]
    S29 --> S30[MARK S = (S1 OR S2 WHICHEVER IS LARGER)]
    S30 --> 2((2))

```

FIG. 8

006T60" 65T9960




FIG. 9

006T60-65T59960




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14

ID 11
POSITION
TYPE
DIRECTION
O-TH VIRTUAL : ID 9 FIRST VIRTUAL : ID12 SECOND VIRTUAL : ID 8 MINUS FIRST VIRTUAL : ID13 MINUS SECOND VIRTUAL : ID12
ID 12
POSITION
TYPE
DIRECTION
:

FIG. 15





FIG. 16





FIG. 17

ID 11
POSITION
TYPE
DIRECTION
O-TH PRIMARY : ID 10 FIRST PRIMARY : ID 9 SECOND PRIMARY : ID 9 MINUS FIRST PRIMARY : ID 12 MINUS SECOND PRIMARY : ID 13 O-TH SECONDARY : ID 9 FIRST SECONDARY : ID 12 SECOND SECONDARY : ID 8 MINUS FIRST SECONDARY : ID 13 MINUS SECOND SECONDARY : ID 12
ID 12
:

FIG. 18




FIG. 19





FIG. 20

006160-6515950



TO FIG. 22

FIG. 21




FIG. 22




FIG. 23




FIG. 24

006T60" 62T5960




FIG. 25

005750" 6575950




FIG. 26




FIG. 27

006T60" 65T5960




FIG. 28

005760" 6575960




FIG. 29




FIG. 30




FIG. 31

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Declaration and Power of Attorney For Patent Application

特許出願宣言書及び委任状

Japanese Language Declaration

日本語宣言書

下記の氏名の発明者として、私は以下の通り宣言します。

As a below named inventor, I hereby declare that:

私の住所、私書箱、国籍は下記の私の氏名の後に記載された通りです。

My residence, post office address and citizenship are as stated next to my name.

下記の名称の発明に関して請求範囲に記載され、特許出願している発明内容について、私が最初かつ唯一の発明者（下記の氏名が一つの場合）もしくは最初かつ共同発明者であると（下記の名称が複数の場合）信じています。

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

APPARATUS AND METHOD FOR MATCHING FINGERPRINT

上記発明の明細書（下記の欄でx印がついていない場合は、本表に添付）は、

the specification of which is attached hereto unless the following box is checked:

☐ 月 日に提出され、米国出願番号または特許協定条約国際出願番号を _____ とし、
（該当する場合） _____ に訂正されました。

☐ was filed on _____
as United States Application Number or
PCT International Application Number
_____ and was amended on
_____ (if applicable).

私は、特許請求範囲を含む上記訂正後の明細書を検討し、内容を理解していることをここに表明します。

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

私は、連邦規則法典第37編第1条56項に定義されるとおり、特許資格の有無について重要な情報を開示する義務があることを認めます。

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Japanese Language Declaration (日本語宣言書)

私は、米国法典第35編119条(a)-(d)項又は365条(b)項に基づき下記の、米国以外の国の少なくとも一ヶ国を指定している特許協力条約365(a)項に基づき国際出願、又は外国での特許出願もしくは発明者証の出願についての外国優先権をここに主張するとともに、優先権を主張している、本出願の前に出願された特許または発明者証の外国出願を以下に、枠内をマークすることで、示しています。

Prior Foreign Application(s)

外国での先行出願

11-292847

Japan

(Number)
(番号)

(Country)
(国名)

(Number)
(番号)

(Country)
(国名)

I hereby claim foreign priority under Title 35, United States Code, Section 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed.

Priority Not Claimed

優先権主張なし

14th/October/1999

(Day/Month/Year Filed)
(出願年月日)

(Day/Month/Year Filed)

(出願年月日)

☐

☐

私は、第35編米国法典119条(e)項に基づいて下記の米国外特許出願規定に記載された権利をここに主張いたします。

I hereby claim the benefit under Title 35, United States Code, Section 119(e) of any United States provisional application(s) listed below.

(Application No.)
(出願番号)

(Filing Date)
(出願日)

(Application No.)
(出願番号)

(Filing Date)
(出願日)

私は、下記の米国法典第35編120条に基づいて下記の米国外特許出願に記載された権利、又は米国を指定している特許協力条約365条(c)に基づき権利をここに主張します。また、本出願の各請求範囲の内容が米国法典第35編112条第1項又は特許協力条約で規定された方法で先行する米国外特許出願に開示されていない限り、その先行米国外出願書提出日以降で本出願書の日本国内または特許協力条約国際提出日までの期間中に入手された、連邦規則法典第37編1条56項で定義された特許資格の有無に関する重要な情報について開示義務があることを認識しています。

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s), or 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code Section 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of application.

(Application No.)
(出願番号)

(Filing Date)
(出願日)

(Status: Patented, Pending, Abandoned)
(現況: 特許許可済、係属中、放棄済)

(Application No.)
(出願番号)

(Filing Date)
(出願日)

(Status: Patented, Pending, Abandoned)
(現況: 特許許可済、係属中、放棄済)

私は、私自身の知識に基づいて本宣言書中で私が行なう表明が真実であり、かつ私の入手した情報と私の信じていることに基づき表明が全て真実であると信じていること、さらに故意になされた虚偽の表明及びそれと同等の行為は米国法典第18編第1001条に基づき、罰金または拘禁、もしくはその両方により処罰されること、そしてそのような故意による虚偽の表明を行なえば、出願した、又は共に許可された特許の有効性が失われることを認識し、よってここに上記のごとく宣誓を致します。

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Japanese Language Declaration

(日本語宣言書)

委任状： 私は下記の発明者として、本出願に関する一切の手続きを米特許商標局に対して遂行する弁理士または代理人として、下記の者を指名いたします。(弁理士、または代理人の氏名及び登録番号を明記のこと)

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith (list name and registration number)

James D. Halsey, Jr., 22,729; Harry John Staas, 22,010; David M. Pitcher, 25,908; John C. Garvey, 28,607; J. Randall Beckers, 30,358; William F. Herbert, 31,024; Richard A. Gollhofer, 31,106; Mark J. Henry, 36,162; Gene M. Garner II, 34,172; Michael D. Stein, 37,240; Paul I. Kravetz, 35,230; Gerald P. Joyce, III, 37,648; Todd E. Marlette, 35,269; Harlan B. Williams, Jr., 34,756; George N. Stevens, 36,938; Michael C. Soldner, P-41,455 and William M. Schertler, 35,348 (agent)

書類送付先

Send Correspondence to:

STAAS & HALSEY
700 Eleventh Street, N.W.
Suite 500
Washington, D.C. 20001

直接電話連絡先： (名前及び電話番号)

Direct Telephone Calls to: (name and telephone number)

STAAS & HALSEY
(202) 434-1500

唯一または第一発明者名	Full name of sole or first inventor	
	Yusaku FUJII	
発明者の署名	日付	Inventor's signature Date
		<i>Yusaku Fujii</i> Sep. 8, 2000
住所	Residence	
	Kawasaki, Japan	
国籍	Citizenship	
	Japan	
私書箱	Post Office Address	
	c/o FUJITSU LIMITED, 1-1, Kamikodanaka	
	4-chome, Nakahara-ku, Kawasaki-shi,	
	Kanagawa 211-8588, Japan	
第二共同発明者	Full name of second joint inventor, if any	
第二共同発明者	日付	Second inventor's signature Date
住所	Residence	
国籍	Citizenship	
私書箱	Post Office Address	

(第三以降の共同発明者についても同様に記載し、署名をすること)

(Supply similar information and signature for third and subsequent joint inventors.)